

Universal Fiber Optic Multi-Signal Extender

Control box transmitter and receiver


Celerity Universal Fiber Optic Multi-Signal Extender (Gateway Red) is abreakthrough for distribution of AV and control signals over fiber optic cable. HDMI 2.1, and USB 3.2 are supported up to 1000 feet over a single Universal Fiber Optic Cable. The combination of these functions in a component with fiber optic connectivity provides superior performance, bandwidth and flexibility for AV professionals to design and install high performance audio, video and control signal distribution systems.



Supporting HDMI 2.1, 48 Gbps and up to 4:4:4 color, Celerity UFO Gateway delivers 100% signal integrity from point to point. HDMI for high definition video and USB 3.2 for video camera and hard drive server.

2 Steps to Fiber Optic Control

With Celerity UFO Gateway, only 2 steps are required - pre-wire and connect. No fiber tools are



needed, this saves time and cost. Now a fiber optic connection can be made fast and reliable. Using the MPO connector on each end of the Celerity fiber optic cable, a secure snap-lock connection is made to the UFO-GTW-RED-8K-TX and UFO-GTW-RED-8K-RX.

The Celerity Universal Fiber Optic Cable is plenum-rated to meet safety certification standards. The Celerity UFO Cable is available in lengths of 35' 40' 50' 60' 80' 100' 130' 160' 200' 500' and 1000'. Celerity UFO Cables are sold separately from the UFO-GTW-RED-8K-TX transmitter and UFO-GTW-RED-8K-RX and receiver. Custom length UFO Cables are available.

Universal Fiber Optic GTW

Specifications

HDMI output

Function UFO-GTW-RFD-8K-TX UFO-GTW-RED-

8K-RX

Control box, transmitter Control box, receiver

up to 1000 ft Celerity fiber optic cable distance up to 1000 ft **HDMI** input

HDMI Type-A

HDMI Type-A

USB* 1, USB 3.2 Type A 1, USB 3.2 Type-B 200mA@5VDC Power 200mA@5VDC

Metal Metal Enclosure

Data rate up to 48 Gbps

4K@120Hz 4:4:4, uncompressed Resolution

or8K@60Hz 4:2:0, uncompressed

Supported features **HDMI High Speed**

HDR HDCP v2.3 **EDID** CEC BT.2020 Deep Color



Included Items UFO-GTW-KIT

Universal Fiber Optic GTW Control box, transmitter (TX)

1 each:

UFO-GTW-RED-8K-TX Mounting bracket

AC/DC power adapter (AC 110V~240V / DC 5V 2A)

User guide

Universal Fiber Optic GTW Control box, receiver (RX)

1 each:

UFO-GTW-RED-8K-RX Mounting bracket

AC/DC power adapter (AC 110V~240V / DC 5V 2A)

Universal Fiber Optic Cable

Available lengths

35ft	10.6m	130ft	39.6m
40ft	12.2m	160ft	48.7m
50ft	15.2m	200ft	60.9m
60ft	18.2m	500ft	152.4m
80ft	24.3m	1000ft	304.8m
100ft	30.4m		

Custom lengths

Available in 50' (15.2m) increments from 250' to 950' (76.2m to 290m)

MPO connector dimension: 7.5mm x 12.7mm x 25.4mm

Fiber optic cable diameter: 3mm in diameter

Plenum rated, OFNP



Pricing subject to change. Please contact Celerity to order.

celeritytek.com 10 goddard irvine ca 92618 949.453.9988